



GUIDES	OUTER	INNER C	INNER F	WEIGHT	TECHNICAL SPECIFICATIONS
6+6 x GN 1/1 80mm spacing	W: 525mm D: 810mm H: 1445mm	W: 330mm D: 540mm H: 508mm	W: 330mm D: 540mm H: 508mm	75 kg	<p>Exterior walls: ABS plastic.</p> <p>Inner container: Welded container in stainless steel.</p> <p>Guides: Stainless steel, pressed from the inner container.</p> <p>Insulation: Polyurethane foam.</p> <p>Door: Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic.</p> <p>Wheels: Hot-dip galvanized steel. 160 mm wheels with rubber tires, two braked and two fixed.</p> <p>Top frame: Stainless steel and PVC corners.</p> <p>Trolley frame: Rejected list of galvanized steel coated with PVC.</p> <p>C: Efficient compact chillers with electronic temperature control AA120/180W, insulation class IP44.</p> <p>F: Efficient convection heating system, with electronic temperature control, insulation class IP 44, 230V/1000W. CE and S mark.</p>
<p>AA120/180W + 230V/550W Product number: 122215-ZCF SDX Thermobox CF180 (6+6 GN 1/1) Single handed grip handle</p> <p>Product number: 122215-XCF SDX Thermobox CF180 (6+6 GN 1/1) Excenter lock</p>					