

THERMOBOX® FF300 – CONVECTION HEATING

hoflandGROOTKEUKEN &
CATERING EQUIPMENT

| GUIDES | OUTER | INNER | WEIGHT | TECHNICAL SPECIFICATIONS |
|---|-----------------------------------|--------------------------------------|--------|--|
| 10+10 x GN 1/1 80mm spacing | W: 920mm D: 770mm H: 1180mm | W: 330+330mm D: 540mm H: 830mm | 120 kg | <p>Exterior walls: ABS plastic.</p> <p>Inner container: Welded container in stainless steel.</p> <p>Guides: Stainless steel, pressed from the inner container.</p> <p>Insulation: Polyurethane foam.</p> <p>Door: Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic.</p> <p>Wheels: Hot-dip galvanized steel. 160 mm wheels with rubber tires, two braked and two fixed.</p> <p>Top frame: Stainless steel and PVC corners.</p> <p>Trolley frame: Reject list of galvanized steel coated with PVC.</p> <p>F: Efficient convection heating system, with electronic temperature control, insulation class IP 44, 230V/1000W. CE mark.</p> |
| <p>2 x 230V/1000W</p> <p>Product number: 122133-ZF</p> <p>SDX Thermobox FF300 (10+10 GN 1/1) Single handed grip handle</p> | | | | |