SDX THERMOBOX





12 12

hofland GROOTKEUKEN& CATERING EQUIPMENT



GUIDES	OUTER	INNER K	INNER F	WEIGHT	TECHNICAL SPECIFICATIONS
10+10 x GN 1/1 80mm spacing	W: 920mm D: 770mm H: 1430mm	W: 330mm D: 540mm H: 828mm	W: 330mm D: 540mm H: 828mm	1 <i>5</i> 0 kg	Exterior walls: ABS plastic. Inner container: Welded container in stainless steel. Guides: Stainless steel, pressed from the inner container.
230V/245W AC + 230V/1000W Product number: 122219-ZKF SDX Thermobox KF300 (10+10 GN 1/1) Single handed grip handle					 Guldes: Stalliess steel, pressed from the inner container. Insulation: Polyurethane foam. Door: Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic. Wheels: Hot-dip galvanized steel. 160 mm wheels with rubber tires, two braked and two fixed. Top frame: Stainless steel and PVC corners. Trolley frame: Reject list of galvanized steel coated with PVC. K: Efficient convection cooling with electronic temperature control 230V/245W, insulation class IP44. F: Efficient convection heating system, with electronic temperature control, insulation class IP 44, 230V/1000W. CE and S mark.

