

# hofland

GROOTKEUKEN &  
CATERING EQUIPMENT



GUIDES	OUTER	INNER K	INNER F	WEIGHT	TECHNICAL SPECIFICATIONS
12+12 x GN 1/1 80mm spacing	W: 930mm D: 770mm H: 1575mm	W: 330mm D: 540mm H: 1000mm	W: 330mm D: 540mm H: 1000mm	150 kg	<p><b>Exterior walls:</b> ABS plastic.</p> <p><b>Inner container:</b> Welded container in stainless steel.</p> <p><b>Guides:</b> Stainless steel, pressed from the inner container.</p> <p><b>Insulation:</b> Polyurethane foam.</p> <p><b>Door:</b> Internal surface made of smooth and seamless stainless steel. Exterior in ABS plastic.</p> <p><b>Wheels:</b> Hot-dip galvanized steel. 160 mm wheels with rubber tires, two braked and two fixed.</p> <p><b>Top frame:</b> Stainless steel and PVC corners.</p> <p><b>Trolley frame:</b> Rejected list of galvanized steel coated with PVC.</p> <p><b>K:</b> Efficient convection cooling with electronic temperature control 230V/190W, insulation class IP44.</p> <p><b>F:</b> Efficient convection heating system, with electronic temperature control, insulation class IP 44, 230V/1000W. CE mark.</p>
<p>230V/190W AC + 230V/1000W</p> <p><b>Product number:</b> 122220-ZKF</p> <p>SDX Thermobox KF360 (12+12 GN 1/1) Single handed grip handle</p>					